Cetus

96634889 CETUS3 M 2000-840 HF RWH

LED 16W CTU3_2000M_840_HF | IEC EN 60598-1 RG 1 | UKCA | IP20 IP44 | halogen | IK06 | 850°C | Ta 0 +25

Cetus

A low height, recessed LED downlight. Suitable for ceiling cut-outs Ø145-180 mm for easy refurbishments or fast initial installations. Remote, pluggable, Fixed output LED driver. Loop in - loop out possible. Body: die-cast aluminium for thermal management. Diffuser: polycarbonate, smooth reflector in white finish with wide beam. Reflector and trim: high quality, highly reflective polycarbonate. Class II electrical, IP44_IP20. Spring clips suitable for ceiling thicknesses from 1 to 35 mm. Complete with 4000K LED

TLG_CTU3_F_M_LED_RWH_Persp.jpg

Dimensions: Ø195 x 100 mm
Luminaire input power: 15.5 W
Luminaire luminous flux: 2048 lm
Luminaire efficacy: 132 lm/W
Weight: 0.56 kg



TLG_CTU3_M_HFM.wmf



TLG_LE_1226.ldt

Lamp position: STD - standard
Light Source: LED
Luminaire luminous flux*: 2048 lm
Luminaire efficacy*: 132 lm/W
Colour Rendering Index min.: 80
Ballast: 1 x 87500989 LC 14/400/35 fixC SRL SNC2
LOR: 1,00 ULOR: 0,00 DLOR: 1,00

Correlated colour temperature: 4000 Kelvin
Chromaticity tolerance (initial MacAdam): 3
Rated median useful life*:
L80 50000h at 25°C
Luminaire input power*: 15.5 W Power factor = 0.56
Dimming: FIX
Maintenance category: C - Closed Top Reflector

This product contains a light source of energy efficiency class C.

All values marked with an * are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C.

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.
© Thorn Lighting